

ML530 Ethernet Access Device

The Actelis® ML530 fiber-based Ethernet Access Device (EAD) complements Actelis' industry-leading EFM over bonded copper solutions, offering the most intelligent Ethernet service delivery on the market.

The ML530 EAD can be used to deliver fully managed, very high bandwidth Ethernet-based service for a variety of network applications, including business-class services, traffic and surveillance, backhaul, and campus and enterprise applications.

The ML530 EAD is interoperable with any standard Ethernet switch, router or hub. Compliant with Metro Ethernet Forum (MEF) specifications, ML530 EADs seamlessly integrate into carrier Ethernet networks, offering five fast Ethernet interfaces and two fiber optical Gigabit Ethernet ports.

The ML530's Small Form Factor (SFP) ports support a large variety of optical interfaces to accommodate short and long distances as needed per applications, with speeds of 100Mbps and up to 1,000Mbps. DS3/E3 uplinks can be used to connect to legacy networks, offering Ethernet over DS3 utilizing a 100/1000Base-FX SFPs port, as well.

The ML530 EAD can be deployed back-to-back in a Point-to-Point topology or in Multipoint topologies with Actelis' Ethernet aggregation switches or any other standard Ethernet switch. The ML530 offers superior performance, extensive functionality and low cost, allowing for advanced Ethernet service distribution.

The ML530 EAD enables service providers to create a complementary, cost-effective, intelligent fiber-based Ethernet access edge with advanced bandwidth control and traffic management features, fully compliant with the MEF 9 and 14 specifications. The ML530 EAD provide 802.1q VLAN-aware wire-speed bridging, double tagging (VLAN stacking) for end-user VLAN transparency, L2 (Ethernet priority) and L3 (ToS/Diff-Serv) classification with four traffic classes, RSTP/STP, ERPS, bandwidth monitoring, and Multicast/Broadcast limiting. The Actelis ML530 EAD can be effectively used by service providers to safely aggregate multiple services or multiple subscribers on the same Ethernet access uplink.

The ML530 is a hardened, RoHS 6 compliant compact unit that is ideal for deployments in outside plants, remote cabinets, basements, as well as customer locations and central offices. Flexible installation options include rack mount, desktop, wall mount, and self-contained NEMA-3 enclosures for pole/wall-mounted or strand-mount applications, and offers remote powering.

The ML530 EADs provide proactive and dynamic tools for enhanced trouble shooting and monitoring capabilities. Advanced Carrier-class EFM OAM, including 802.3ah, CFM (802.1ag) and Y.1731 (ITU), are incorporated, offering both physical link as well as service level end-to-end advanced troubleshooting mechanisms.

The Actelis ML530 EAD ensures a high level of security, enabling safe and protected communication that supports SSH, Radius and additional advanced capabilities.

The ML530 EADs can be managed In- and Out-of-Band by the MetaASSIST™ View graphical craft application and via the multi-platform Element Management System, MetaASSIST EMS. The management protocols include standard command line interface and SNMP using standard MIBs for seamless integration with third-party Network Management Systems (NMS).



Highlights

- Standards-based IEEE 802.3ah Ethernet in the First Mile (EFM) transport over Fiber
- MEF CE 1.0 - MEF 9, 14
- Multiple fiber connection types
- Long-haul Optics for up to 120 km
- Carrier Class OAM, including Y.1731, CFM, and EFM OAM
- EFM Enhanced Security capabilities
- NEBS III, FCC, UL, CE
- Environmentally Hardened

Applications

- Transparent LAN Service
- Fast Internet Access
- Metro Ethernet Extension
- Private Campus Network Intra-Connection
- MDU/MTU Backhaul
- DSLAM Backhaul
- WiFi and Cellular Backhaul (Radio Access Network)
- Leased Lines Replacement

Markets Served

- ILECs, CLECs, IOCs, PTTs, and Alternative Carriers
- Federal, State and Local Government Agencies
- Education, Health Care, Utilities, and Private Campuses



Specifications

Interfaces

Ethernet (Network/User)

- **10/100Base-T:** 4 ports, Connector: RJ45, Auto-MDIX
- **100/1000Base-FX:** 2 ports, Connector: SFP Based, MSA compliant

Management (Out-of-Band)

- **10/100Base-T:** Connector: RJ45, Auto-MDIX
- **Craft EIA RS-232 (DCE):** Connector: DB9

Ethernet Bridge Features

- **Bridging:** IEEE 802.1q
- **Forwarding Database size:** 8K MAC addresses
- **Aging:** Configurable
- **MAC Limiting and Filtering**
- **Multicast/Broadcast Control**
- **Port based VLAN Stacking (Q-in-Q)**
- **VLANs:** 256, in range of {1-4095}
- **RSTP, STP:** IEEE 802.1d
- **Link Aggregation:** IEEE 802.3, L2 balancing
- **ERPS:** ITU-T G.8032
- **Provider Bridges:** IEEE 802.1ad
- **LLDP:** IEEE 802.1ab
- **IGMP Snooping:** RFC 4541, V1/V2 RFC 1112/2236
- **EFM OAM:** IEEE 802.3ah clause 57
- **CFM/MEF OAM:** IEEE 802.1ag, ITU Y.1731

Quality of Service Features

- **Classes of Service** (queues per port): 4
- **Scheduler:** WFQ, SP
- **Classification:** L2 802.1p/Q priorities, L3 ToS/DiffServ

Management

Applications

- **EMS:** MetaASSIST EMS
- **Craft GUI:** MetaASSIST View

Protocols

- IPv4 and IPv6
- **DHCP Client:** RFC 2132
- **ACS Client, CWMP:** TR-069
- **Command Line Interface:** TL1, CLI
- **Remote Access:** Telnet
- **SNMP:** V3, V2C, V1
- **Radius Authentication:** RFC 2865
- **Secure Access (option):** SSH v2
- **Time Synchronization:** SNTP v3
- **Web Access:** HTTP
- **File transfer:** FTP, TFTP
- **Syslog:** RFC 3164

Front Panel Indicators (LEDs)

- Power
- Status
- Alarm
- ACT (Activity)
- LNK (Link) per Ethernet

Alarm Contacts

- **Terminal Block:** 2 Input, 1 Output

Physical

- **Dimensions:** Height: 1.6" / 40mm (1U), Depth: 11.0" / 280mm, Width: 8.4" / 213mm
- **Weight:** 3.75 lbs / 1.7 Kg
- **Mounting Rack:** 2 units in 19", 23" or ETSI racks Desktop, Wall Mount
- **Power DC:** -48/-60 VDC nominal, 10 Watt, **Power AC:** 90-264 VAC, 47-63 Hz, 17-21 Watt

Environmental

- **Operating Temp:** -40° to +74°C*
- **Storage Temp:** -40° to +75°C
- **Relative humidity:** Up to 95%, non-cond.

*Tested in accordance with NEMA temperature requirements

Regulatory Certifications/Compliance

Metro Ethernet Forum

- CE 1.0 - MEF 9, 14

Safety

- UL 60950, CSA C22.2 60950
- EN 60950-1, IEC 60950-1

EMC

- FCC Part 15 Class B
- ICES-003 Class B
- ETSI EN 300 386 Class B
- ETSI ETS 300 132-2
- ITU-T K.20, K.21

NEBS

- Level III (GR-1089-CORE, GR-63-CORE)

CE

- EMC and Safety

Environmental

- GR-63-CORE
- ETSI ETS 300 019



Corporate Headquarters
Actelis Networks, Inc.
47800 Westinghouse Drive
Fremont, CA 94539
t. +1 510-545-1045 or toll-free in U.S. 1-866-ACTELIS

Company and General Information: info@actelis.com
Asia Pacific Sales: apacsales@actelis.com
Central and Latin America Sales: calasales@actelis.com
Europe, Middle East and Africa Sales: emeasales@actelis.com
North America Sales: nasales@actelis.com